

TRUSTY STEP SYSTEMS INC.

5086 Empire Dr
Burnaby BC V5B 1M9
604-291-1855

Fax (604) 648-8270
Email:info@trustystepsystems.com
www.trustystepsystems.com

774 Victoria Street
Kamloops, BC V2C 2B6
877-291-1855

APPLICATION INSTRUCTIONS FOR TRUSTY STEP NO. 1001

READ PRECAUTIONARY LABEL BEFORE USING

- 1) ALWAYS wear rubber gloves, goggles and ventilate the area.
- 2) Be careful not to allow No.1001 to come in contact with any surface other than the one being treated.
- 3) When pouring No.1001 from one container to another, be careful of splash
- 4) The floor should be clean and dry before applying No.1001

No. 1001 WILL WORK ON ALL OF THE FOLLOWING SURFACES (Do not treat painted or sealed surfaces)

- | | |
|-------------------|------------------------|
| 1) Quarry Tile | 5) Concrete |
| 2) Ceramic Tile | 6) Marble |
| 3) Porcelain Tile | 7) Granite |
| 4) Terrazzo | 8) Chicklet Floor Tile |

One gallon of No.1001 will cover between 350 and 400 square feet.

We suggest that no more than 200 square feet be done per person at a time.

Example: Two people can treat 400 square feet at once, 3 could do 600 square feet.

Some of the following factors may cause you to use more No.1001:

- | | | |
|------------------------|-------------------------|------------------|
| 1) Condition of grout | 3) Cleanliness of floor | 5) Tilt of floor |
| 2) Ventilation in area | 4) Drain system | |

NOTE: In some instances, No.1001 may reduce some of the gloss, change the color, make the surface lighter or darker or cause spots to appear on the treated surface. Trusty Step Systems is not responsible for any of these conditions, even if sample tiles have been treated beforehand.

ALWAYS test a small obscure area to determine the length of treatment time and to determine the amount of gloss that may be removed or any other change in appearance. Because of their nature, natural stone, such as Marble and Granite may be lighter and/or darker in some areas, after the application.

TESTING PROCEDURES TO DETERMINE TREATMENT TIME & CHANGE IN APPEARANCE

- 1) Locate a one square foot area in an obscure location
- 2) Pour a few ounces of No.1001 on the floor.
- 3) Spread No.1001 with a sponge. Continue spreading No.1001 for entire treatment time, otherwise No.1001 will congeal and cause spots to appear on the tile when the job is completed.
- 4) Add additional No.1001 as needed to ensure that the surface is thoroughly wet during the **ENTIRE** treatment time.
- 5) After 30 min. rinse with water and check for appearance and to see if tile is slip-resistant. If tile is not satisfactory, continue applying No.1001 and inspect for slip-resistance and appearance every 15 minutes. (Treatment time will be 30-60 minutes, average treatment time is 30 min.)
- 6) Rinse tile thoroughly with water after No.1001 application

EQUIPMENT AND SUPPLIES REQUIRED:

- 1) No.1001 Trusty Step Anti Slip Floor Treatment
- 2) Squeegee
- 3) Floor Applicator
- 4) Hose
- 5) Wet Vacuum

SAFETY EQUIPMENT:

- 1) Rubber Gloves
- 2) Dust Mask
- 3) Safety Glasses

APPLICATION INSTRUCTIONS

- 1) Sweep floor clean, wash thoroughly and let dry.
- 2) Pour about 8 ounces No.1001 directly onto floor.
- 3) Immediately spread No.1001 evenly over floor with floor applicator.
- 4) Continue spreading & moving No.1001 for **ENTIRE** treatment time. Failure to spread & move No.1001 will allow it to congeal and cause spots to appear when the job is completed. Keep evenly wet with No.1001 during the **ENTIRE** treatment time. You may walk on the floor during the application.
- 5) After treatment time, rinse one square foot with water. Push your shoe across rinsed surface to test slip resistance. If satisfactory, rinse entire floor with clean water using a hose or bucket. Continue rinsing until all traces of No.1001 are gone. If not satisfactory, continue applying No.1001 to floor for an additional time until desired results are achieved. Then rinse with water as above.
- 6) Squeegee floor dry. Use wet vacuum or mop if there is no drain.
- 7) Floor is now ready to be walked on and will remain slip-resistant for 3 years – GUARANTEED

See website at www.trustystepsystems.com and click on “video” for visual instructions.

CAUTION:

Avoid applying No.1001 on any surface in direct sunlight. The heat will cause the product to congeal, thereby causing spots. Warm tiles should be cooled with water before applying the product and the remaining water should then be removed. The surface can be damp not wet.

Warning

Keep out of reach of children. Causes severe eye irritation on contact. Severe skin irritation on prolonged contact. Vapors are harmful and irritate the respiratory system. Ingestion causes severe irritation and burns of the gastrointestinal tract.

Handling Precautions

Read all instructions before use. Handle carefully avoiding contact with eyes, skin or clothing. Wear chemical goggles and acid proof rubber or vinyl gloves. Use with adequate ventilation. Do not take internally. Use only plastic containers to transfer, hold and apply the product. Do not allow to come in contact with glass or metal.

First Aid

Eyes: Causes eye burns. Immediately flush with large amounts of water for no less than 15 minute. Get immediate medical attention.

Skin: Causes skin burns. Immediately remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If skin irritation persists see a physician. Wash and dry all contaminated clothing before reuse. Discard contaminated shoes, belts and non-washable items.

Inhalation: Causes respiratory tract burns. Remove patient to fresh air. If breathing with difficulty give oxygen. If not breathing give artificial respiration. For heavy exposure get immediate medical attention.

Ingestion: Drink lots of water, milk or milk of magnesia. Do not induce vomiting. Get immediate medical attention.

Material Safety Data Sheet can be downloaded at http://www.trustystepsystems.com/files/Up_load_files/msds_1001.pdf