

# TRUSTY STEP SYSTEMS INC.

Phone: 604-291-1855  
Toll free: 877-291-1855  
info@trustystepsystems.com  
www.trustystepsystems.com  
Vancouver – Kamloops – British Columbia

## TRUSTY STEP #1001 ANTI-SLIP FLOOR TREATMENT

### FEATURES:

Microscopically etches an invisible tread on the treated surface. One treatment makes the floor slip-resistant for a minimum of three years. Can be used indoors or outdoors

### FOR USE ON:

Ceramic, porcelain & quarry tile, marble, granite, terrazzo and cement.

### TYPICAL APPLICATIONS:

Restaurants, hotels, supermarkets, hospitals, nursing homes, shopping centers, health clubs, pools, etc.



### APPLICATION INSTRUCTIONS:

- Sweep floor clean, wash thoroughly and let dry.
- Pour about 8 ounces of #1001 directly onto floor.
- Immediately spread #1001 evenly over floor with floor applicator
- Continue spreading & moving #1001 for **ENTIRE** treatment time. Failure to spread & move #1001 will allow it to congeal and cause spots to appear when the job is completed. You may walk on the floor during application.
- After treatment time, rinse one square foot with water. Push your shoe across rinsed surface to test slip resistance. If satisfactory, rinse entire floor with clean water using a hose or a bucket. Continue rinsing until all traces of #1001 are gone. If not satisfactory, continue applying #1001 to floor for an additional time until desired results are achieved. Then rinse with water as above.
- Squeegee floor dry. Use wet vacuum or mop if there is no drain.
- Floor is now ready to be walked on and will remain slip-resistant for 3 years - **GUARANTEED**

### THREE YEAR GUARANTEE

TRUSTY-STEP ANTI-SLIP FLOOR TREATMENT is guaranteed to raise the static coefficient of friction on hard mineral surfaces (ceramic, quarry & porcelain tile, marble, granite, terrazzo and cement) to 0.6 for a minimum period of 3 years.

Routine cleaning and maintenance to remove grease, oil or other substances is required.

This Guarantee shall only provide for re-treatment of any surface that is found to lose its non-slip effectiveness. This Guarantee shall be void if the static coefficient of friction of a treated surface falls below 0.6 because of the presence of a foreign substance. It does not cover compensation for injuries or losses due to slip/fall accidents or other direct, indirect or consequential damages resulting from the failure of any treated surface to retain a static coefficient of friction of 0.6.

### PACKAGING & PRICING:

- |   |           |                       |
|---|-----------|-----------------------|
| • 4 oz Sample Kit - Will Treat 10 Sq. Ft.   | \$30.00   | plus shipping & taxes |
| • 32 oz Container - Will Treat 90 Sq. Ft.   | \$120.00  | plus shipping & taxes |
| • 128oz Gallon - Will Treat 350 Sq. Ft.     | \$395.00  | plus shipping & taxes |
| • Box - 4 Gallons - Will Treat 1400 Sq. Ft. | \$1395.00 | plus shipping & taxes |
| • Floor Applicator & Pad                    | \$25.00   | plus shipping & taxes |

For additional information please contact [sales@trustystepsystems.com](mailto:sales@trustystepsystems.com) or call 877-291-1855